

TECHNICAL DATA INDULVENT connect

INDULVENT connect

		2-pipe		4-pipe	
		Cooling		Cooling	Heating
OPERATING RANGE					
Temperature	°C	+ 5 to + 40		+ 5 to + 40	
Relative humidity	RH %	30 to 70		30 to 70	
DIMENSIONS HOUSING ¹⁾					
Height	(total)	mm	335	335	
Width Size	625 (600)	mm	596 (571)	596 (571)	
Length Size	625 (600)	mm	594 (569)	594 (569)	
DIMENSIONS FRONT PLATE					
Height		mm	12	12	
Width Size	625 (600)	mm	623 (598)	623 (598)	
Length Size	625 (600)	mm	623 (598)	623 (598)	
HEAT EXCHANGER – WATER AS OPERATING MEDIUM					
Operating limits water temperature	°C	+ 5 to + 65		+ 5 to + 65	
Test pressure	bar	10		10	
Nominal water flow rate	l/h	250	250	150	
Nominal pressure drop	kPa	7,4	6,5	2,2	
Supply/return water connection pipe	-	½" male thread		½" male thread	
Water content	l	1,8		1,8	
CONDENSATE PUMP					
Condensate connection (pressure line)	mm	6 x 1,5		6 x 1,5	
Condensate pump delivery head / flow rate	m / l/h	3,5 / 6	3,5 / 6	-	
ELECTROTECHNICAL DATA					
Mains connection	V / Hz	230 / 50		230 / 50	
IP rating (housing / radial fan)	-	IP20/IP54		IP20/IP54	
Power requirement of condensate pump (Operation / Standby)	W	8 / 1		8 / 1	
Nominal fan power consumption ²⁾	W	30		30	
GENERAL					
Operating weight	kg	33		33	

¹⁾without frontplate

²⁾Power requirement at control voltage 10 VDC